

SAFETY DATA SHEET

1. Identification

Material name: Horizon® Matte Coat
Material: TBS520-600 805

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Barrier Solutions
6402 E. MAIN STREET
REYNOLDSBURG OH 43068
US

Contact person: EH&S Department
Telephone: 216-292-5000
Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Acute toxicity (Inhalation - dust and mist)	Category 4
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	31.15 %
Acute toxicity, dermal	36.17 %
Acute toxicity, inhalation, vapor	100 %
Acute toxicity, inhalation, dust or mist	71.81 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Harmful if inhaled.
May cause cancer.

Precautionary Statements

Prevention: Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

Storage: Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Titanium dioxide	13463-67-7	3 - 7%
Propylene glycol	57-55-6	3 - 7%
Cellulose	9004-34-6	1 - 5%
2-Propanol	67-63-0	1 - 5%
Magnesite	546-93-0	0.1 - 1%
Heavy paraffinic distillate	64741-88-4	0.1 - 1%
Clay	1332-58-7	0.1 - 1%
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	0.1 - 1%
Aluminum oxide	1344-28-1	0.1 - 1%
Ammonium hydroxide	1336-21-6	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Inhalation: Move to fresh air.

Skin Contact: Wash skin thoroughly with soap and water. Get medical attention if symptoms occur.

Eye contact: Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: No data available.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Cellulose	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Cellulose - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Cellulose - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
2-Propanol	TWA	200 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	400 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	400 ppm 980 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Magnesite - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Magnesite - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Heavy paraffinic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (2011)
Heavy paraffinic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Heavy paraffinic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Clay - Respirable fraction.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Clay - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles per	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)

		cubic foot of air	
Clay - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Clay - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	US. ACGIH Threshold Limit Values (2011)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.05 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (03 2016)
	OSHA_ACT	0.025 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (03 2016)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	PEL	0.05 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Aluminum oxide - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Aluminum oxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Aluminum oxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Aluminum oxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Ammonium hydroxide	STEL	35 ppm	US. ACGIH Threshold Limit Values (2011)
	TWA	25 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	50 ppm 35 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	Type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Propylene glycol - Aerosol.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Propylene glycol - Vapor and aerosol.	TWA	50 ppm 155 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Cellulose - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Cellulose - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Cellulose	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Cellulose - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
2-Propanol	STEL	400 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	200 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
2-Propanol	TWA	200 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	400 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
2-Propanol	STEL	500 ppm 1,230 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	400 ppm 983 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Heavy paraffinic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Heavy paraffinic distillate - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Heavy paraffinic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
2-Propanol (acetone: Sampling time: End of shift at end of work week.)	40 mg/l (Urine)	ACGIH BEI (03 2013)

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: Wear suitable protective clothing.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	Gray
Odor:	Mild
Odor threshold:	No data available.
pH:	9 - 10
Melting point/freezing point:	< 0 °C < 32 °F
Initial boiling point and boiling range:	100 °C 212 °F
Flash Point:	> 93 °C > 200 °F (Rapid Tester, DIN EN ISO 3679)
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.0312
Solubility(ies)	
Solubility in water:	Soluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Strong acids. Strong bases.

Hazardous Decomposition Products: Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation: In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.

Skin Contact: May be harmful in contact with skin.

Eye contact: Eye contact is possible and should be avoided.

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Calcium carbonate LD 50 (Rat): > 2,000 mg/kg

Titanium dioxide LD 50 (Rat): > 5,000 mg/kg

Propylene glycol LD 50 (Rat): 22,000 mg/kg

Cellulose LD 50 (Rat): 5,001 mg/kg

2-Propanol LD 50 (Rat): 5.84 g/kg

Magnesite LD 50 (Rat): > 2,000 mg/kg

Heavy paraffinic distillate LD 50 (Rat): > 5,000 mg/kg

Clay LD 50 (Rat): > 5,000 mg/kg

Aluminum oxide LD 50 (Rat): > 10,000 mg/kg

Ammonium hydroxide LD 50 (Rat): 350 mg/kg

Dermal**Product:** ATEmix: 4,150.14 mg/kg**Inhalation****Product:** ATEmix: 3.05 mg/l**Repeated dose toxicity****Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Specified substance(s):**

Calcium carbonate	in vivo (Rabbit): Not irritant Experimental result, Key study
Titanium dioxide	in vivo (Rabbit): Not irritant Experimental result, Supporting study
Propylene glycol	in vivo (Rabbit): Not irritant Experimental result, Key study
2-Propanol	in vivo (Rabbit): Not Classified Experimental result, Key study
Magnesite	In vitro (Human, in vitro reconstituted epidermis model): Not irritant Experimental result, Key study
Heavy paraffinic distillate	in vivo (Rabbit): Not irritant Experimental result, Key study
Aluminum oxide	in vivo (Rabbit): Not irritant Experimental result, Key study

Serious Eye Damage/Eye Irritation**Product:** No data available.**Specified substance(s):**

Calcium carbonate	Rabbit, 24 - 72 hrs: Not irritating
Titanium dioxide	Rabbit, 24 hrs: Not irritating
2-Propanol	Rabbit, 24 hrs: Category 2: Causes serious eye irritation
Magnesite	Reconstituted Corneal Epithelium model, 10 min: Not irritating
Heavy paraffinic distillate	Rabbit, 24 hrs: Not irritating
Aluminum oxide	Rabbit, 24 hrs: Not irritating

Respiratory or Skin Sensitization**Product:** No data available.**Carcinogenicity****Product:** No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
2-Propanol	Overall evaluation: Carcinogenic to humans. Overall evaluation: Not classifiable as to carcinogenicity to humans.
Heavy paraffinic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.
Crystalline Silica (Quartz)/ Silica Sand	Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Heavy paraffinic distillate	Known To Be Human Carcinogen.
Crystalline Silica (Quartz)/ Silica Sand	Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro
Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity
Product: No data available.

Specific Target Organ Toxicity - Single Exposure
Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure
Product: No data available.

Aspiration Hazard
Product: No data available.

Other effects: No data available.

12. Ecological information**Ecotoxicity:****Acute hazards to the aquatic environment:****Fish****Product:** No data available.**Specified substance(s):**Propylene glycol LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 29,485 - 39,339 mg/l Mortality2-Propanol LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 11,130 mg/l Mortality**Aquatic Invertebrates****Product:** No data available.**Specified substance(s):**Titanium dioxide EC 50 (Water flea (*Daphnia magna*), 48 h): > 1,000 mg/l IntoxicationPropylene glycol EC 50 (Water flea (*Daphnia magna*), 48 h): > 10,000 mg/l Intoxication2-Propanol LC 50 (Water flea (*Daphnia magna*), 24 h): > 10,000 mg/l Mortality
LC 50 (Brine shrimp (*Artemia salina*), 24 h): > 10,000 mg/l Mortality**Chronic hazards to the aquatic environment:****Fish****Product:** No data available.**Specified substance(s):**Propylene glycol NOAEL (*Pimephales promelas*, 7 d): 11,530 mg/l Experimental result, Not specified**Aquatic Invertebrates****Product:** No data available.**Toxicity to Aquatic Plants****Product:** No data available.**Persistence and Degradability****Biodegradation****Product:** No data available.**BOD/COD Ratio****Product:** No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Propylene glycol Log Kow: -0.92

2-Propanol Log Kow: 0.05

Mobility in soil: No data available.

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Acrylonitrile	Liver Central nervous system Flammability Eye irritation Skin irritation Skin sensitization Respiratory irritation Cancer Acute toxicity

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
2-Propanol	100 lbs.
Ammonium hydroxide	1000 lbs.
Sodium nitrite	100 lbs.
Isobutane	100 lbs.
n-(3,4-dichlorophenyl)- n,n-dimethylurea	100 lbs.
Ammonia	100 lbs.
Methyl benzimidazole-2- yl carbamate	10 lbs.
Acrylamide	5000 lbs.
Acrylonitrile	100 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

- Immediate (Acute) Health Hazards
- Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Ammonia	100 lbs.	500 lbs.
Acrylamide	5000 lbs.	- - -
Acrylonitrile	100 lbs.	10000 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
2-Propanol	100 lbs.
Ammonium hydroxide	1000 lbs.
Sodium nitrite	100 lbs.
Isobutane	100 lbs.
n-(3,4-dichlorophenyl)- n,n-dimethylurea	100 lbs.
Ammonia	100 lbs.
Methyl benzimidazole-2- yl carbamate	10 lbs.
Acrylamide	5000 lbs.
Acrylonitrile	100 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Ammonia	500lbs
Acrylamide	500lbs
Acrylonitrile	500lbs
Calcium carbonate	10000 lbs
Titanium dioxide	10000 lbs
Propylene glycol	10000 lbs
Cellulose	10000 lbs
2-Propanol	10000 lbs
Magnesite	10000 lbs
Heavy paraffinic distillate	10000 lbs
Clay	10000 lbs
Crystalline Silica (Quartz)/ Silica Sand	10000 lbs
Aluminum oxide	10000 lbs
Ammonium hydroxide	10000 lbs

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>
2-Propanol

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Isobutane	lbs
Ammonia	lbs
Ammonia	lbs
Acrylonitrile	lbs

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65



WARNING

Cancer and Reproductive Harm - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

<u>Chemical Identity</u>
Calcium carbonate
Titanium dioxide
Propylene glycol
Cellulose
2-Propanol
Heavy paraffinic distillate
Crystalline Silica (Quartz)/ Silica Sand

US. Massachusetts RTK - Substance List

Chemical Identity

Calcium carbonate
Titanium dioxide
Cellulose
2-Propanol
Crystalline Silica (Quartz)/ Silica Sand
Ammonia
Acrylamide
Acrylonitrile

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Calcium carbonate
Titanium dioxide
Propylene glycol
Cellulose
2-Propanol

US. Rhode Island RTK

Chemical Identity

Calcium carbonate
Titanium dioxide
Propylene glycol
Cellulose
2-Propanol

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC:

Regulatory VOC (less water and
exempt solvent) : 66 g/l

VOC Method 310 : 4.36 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	One or more components in this product are not listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date:	10/05/2018
Version #:	2.1
Further Information:	No data available.

Disclaimer:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.